



5 IN SCHED 40 PIPE  
(Ø5.56 OD X Ø5.05 ID)

MOUNTING PLATE

**FINISH: CAGE SHALL HAVE A HOT DIPPED GALVANIZED FINISH PER ASTM A 123 SPECIFICATIONS.**

lyte poles  
a DWR company

P.O. Box 340  
Eastpointe, MI 48021  
P: (586) 771-4610 | F: (586) 771-5527  
www.lytepoles.com

DRAWN: M. HARVALA	3/25/2015	SOME GEOGRAPHICAL AREAS HAVE SPECIAL WIND CONDITIONS THAT CAN CREATE WIND INDUCED VIBRATIONS CAUSING A FATIGUE PROBLEM. NO METHOD HAS YET BEEN FOUND FOR PREDICTING DESTRUCTIVE LIGHTING POLE VIBRATION. THESE CONDITIONS ARE UNIQUE AND CANNOT BE GUARANTEED AGAINST, AND ARE THE RESPONSIBILITY OF A LOCAL SITE ENGINEER.
CHECKED	DATE:	
REVISION:	DATE:	
APPROVED:	DATE:	
QUOTE:		TITLE:
S.O.#		CATALOG:
REF:	SCALE: NONE	DWG NO: PLT-21
		SIZE D
		SHEET 1 OF 1

